



## PERSONALIZED CAPABILITIES TO REDEFINE YOUR WORKFLOW

Canon imageRUNNER systems are known for their innovation and versatility. Now Canon takes this concept one step further with the imageRUNNER 3045 device-offering a new element of personalization to truly meet the individual workflow needs of every user in your office.

With digital copying and Mail Box features, optional Universal Send and network printing, a choice of finishing options, as well as new system features that allow you to customize the device and streamline your workflow, the imageRUNNER 3045 device is built for the department, but designed for the individual.

25% - 400% (in 1% Increments)

**MAIN UNIT** 

Imaging System: Developing System:

Fixing System: Acceptable Originals:

Max. Original Copy Size: Min. Copy Size:

Memory Standard:

Optional:

Max. Copy Reservation: Max. Mail Boxes Supported: Actual Resolution:

Interpolated Resolution:

**Exposure Control:** 

Halftone:

Copy/Print Speed (Letter):

First-Copy Time:

Warm-Up Time:

Multiple Copies: Document Feeding Method:

Paper Source Standard:

> Optional: Maximum:

Acceptable Paper Sizes Upper Cassette:

> Lower Cassette: Stack Bypass:

Acceptable Paper Weight Cassettes: Stack Bypass: Duplexing:

17 lb. to 20 lb. Bond 17 lb. to 32 lb. Bond Duplexing

Monochrome Digital Multifunction

**Imaging System** Laser Dry Electrostatic Transfer Dry Monocomponent Toner

Projection

RAPID Fusing System™ Sheets, Books, and 3-Dimensional Objects (up to 4.4 lb.)

3-7/8" x 5-7/8" (Stack Bypass)

512MB RAM + 20GB HDD (Shared)

256MB RAM (768MB RAM

Maximum) 10 lobs 100

600 x 600 dpi 1200 x 600 dpi (Copy) 2400 x 600 dpi (Print)

256 Gradations of Gray (Continuous Tone) Automatic or Manual (9 Levels)

Up to 45 ppm Approx. 3.9 Seconds (From Platen

Approx. 5.9 Seconds (From DADF)

Approx. 30 Seconds or Less From Main Power Off

Approx. 10 Seconds or Less From Sleep Mode

1 - 9.999

50-Sheet Duplexing Automatic Document Feeder (Standard)

**Dual 550-Sheet Paper Cassettes** 50-Sheet Stack Bypass Dual 550-Sheet Paper Cassettes

2.700-Sheet Paper Deck 4.950 Sheets

Legal, Letter, Letter-R, Statement-R. Executive

11" x 17", Legal, Letter, Letter-R, Statement-R. Executive 11" x 17", Legal, Letter, Letter-R, Statement-R. Executive, Free Size (3-7/8" x 5-7/8" to 11-5/8" x 17").

and Envelopes

Standard Automatic Trayless

Magnification Standard Mode:

25%, 50%, 64%, 73%, 78% Preset Reduction: Preset Enlargement: 121%, 129%, 200%, 400%

700m Mode Platen:

DADF: 25% - 200% (in 1% Increments) Network Interface 10/100Base-TX (RJ-45), Connections:

IISB 2.0 High Speed Dimensions (H x W x D): 34-3/4" x 22-1/4" x 27-5/8" (883mm x 565mm x 700mm)

Weight: 183 lb. (83kg) Power Requirements: 120V AC, 60Hz, 10A Power Consumption: 1.35kW (Max.) NEMA 5-15P

Toner (Estimated Yield): 24,000 Impressions at 6% Image Coverage

**Duplexing Automatic Document Feeder** 

Acceptable Originals: 11" x 17", Legal, Letter, Letter-R, Statement-R

Acceptable Weights

One-Sided Scanning: 11 lb. to 32 lb. Bond Two-Sided Scanning: 13 lb. to 32 lb. Bond 50 Sheets (20 lb. Bond) Paper Capacity: Original Scanning Speed: Up to 45 ipm (LTR) Dimensions (H x W x D): 8-7/8" x 22-1/4" x 21-1/4" (122mm x 565mm x 538mm)

Approx. 18.7 lb. (8.5kg) Weight: Power Consumption: Approx. 30W

**OPTIONAL ACCESSORIES** 

**Cassette Feeding Unit-Y3** 

Acceptable Paper Sizes: 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive

Paper Capacity: **Dual 550-Sheet Cassettes** (1,100 Sheets at 20 lb. Bond)

 $(80g/m^2)$ 

Acceptable Paper Weight: 17 lb. to 20 lb. Bond Dimensions (H x W x D):

9-7/8" x 22-1/4" x 27-5/8" (252mm x 565mm x 700mm)

Power Consumption: Approx. 20W Approx. 50.7 lb. (23kg) Weight:

Paper Deck-Q1

Acceptable Paper Size: Letter

Paper Capacity: 2,700 Sheets (20 lb. Bond)

 $(80g/m^2)$ 

Acceptable Paper Weight: 17 lb. to 20 lb. Bond Dimensions (H x W x D): 18-5/8" x 14-5/8" x 23-1/4" (473mm x 372mm x 591mm)

36-7/8" x 27-5/8" (937mm x Installation Space (W x D):

700mm)

Weight: Approx. 65.3 lb. (29.6kg) **Envelope Feeder Attachment-C2** 

Acceptable Envelopes: COM10, Monarch, DL, ISO-B5,

ISO-C5, Yougata4 Copy Speed: Up to 12 cpm

50 Sheets or 30mm in Height Dimensions (H x W x D): 3-3/4" x 22-1/4" x 20-1/2" (95mm x 565mm x 521mm)

Approx. 6.6 lb. (3kg) Weight:

Inner 2-Way Tray-D1

Number of Travs: Two

Acceptable Paper Sizes: 11" x 17", Legal, Letter, Letter-R,

Statement-R, Executive, Envelope, Freesize (3-7/8" x 5-7/8"

to 11-3/4" x 17") Acceptable Paper Weight: 17 lb. to 32 lb. Bond

Paper Capacity Per Tray

Upper Tray:

50 Sheets (Other Sizes) Lower Tray: 250 Sheets (LTR), 100 Sheets (Other Sizes)

100 Sheets (LTR),

Dimensions (H x W x D): 6" x 7" x 21-1/2" (151mm x 176mm x 546mm)

Installation Space (W x D): 34" x 27-5/8" (862mm x 700mm) (When Stack Bypass is Extended)

Power Consumption: Approx. 16W Attachable Accessories: Copy Tray-J1

Finisher-S1

Number of Trays: One (Second Tray Optional) Acceptable Paper Sizes: 11" x 17", Legal, Letter, Letter-R,

Statement-R, Executive, Envelope, Freesize (3-7/8" x 5-7/8" to 11-3/4" x 17")

Acceptable Paper Weight: 17 lb. to 32 lb. Bond

Paper Capacity Per Tray Non-collate, Collate, Group Mode:

1,000 Sheets (Letter, Statement-R)

500 Sheets (11" x 17", Legal, Letter-R)

Staple Mode: 1,000 Sheets/30 Sets (Letter) 500 Sheets/30 Sets (11" x 17",

Legal, Letter-R)

Paper Capacity Per Tray (with Additional Finisher Tray-B1)

Non-collate, Collate,

Staple Mode:

Group Mode: 300 Sheets Per Tray (Letter,

Statement-R)

150 Sheets Per Tray (11" x 17",

Legal, Letter-R) 300 Sheets/30 Sets Per Tray (Letter)

150 Sheets/30 Sets Per Tray

(11" x 17", Legal, Letter-R)

Staple Position

11" x 17" (Landscape), Legal Top Left Corner: (Landscape), Letter, Letter-R Top Right Corner: 11" x 17" (Portrait), Legal

(Portrait)

## SPECIFICATIONS





Max. Stapling Capacity:	50 Sheets (Letter) 30 Sheets (11" x 17", Legal, Letter-R)
Dimensions (H x W x D):	12-3/8" x 23-1/2" x 21-3/4" (315mm x 598mm x 552mm)
Installation Space (W x D):	41-1/8" x 27-5/8" (1044mm x 700mm)
Power Consumption:	Approx. 45W (When Additional Finisher Tray-B1 is Attached)
Attachable Accessories:	Additional Finisher Tray-B1 Puncher Unit-R1 Copy Tray-J1

Additional Finisher Tray-B1 Tray Capacity: See Finisher-S1 Specifications

Dimensions (H x W x D): 3-1/8" x 7-7/8" x 15-5/8" (80mm x 200mm x 395mm) Approx. 3.7 lb. (1.7kg) Weight:

Puncher Unit-R1 (Option for Finisher-S1)

Acceptable Paper Sizes: 11" x 17", Legal, Letter, Letter-R

Acceptable Paper Weight: 17 lb. to 32 lb. Bond Punch Type Two Holes: Legal, Letter-R

Three Holes: 11" x 17", Letter **Punch Waste Capacity** Approx. 2,500 Sheets Two Holes:

Three Holes: Approx. 1,500 Sheets 6-7/8" x 19-7/8" x 5-1/8" Dimensions (H x W x D): (175mm x 505mm x 130mm)

Weight: Approx. 8.6 lb. (3.9kg)

Finisher-AE1/Saddle Finisher-AE2

Number of Trays: 2 Trays Acceptable Paper Sizes: 11" x 17", Legal, Letter, Letter-R,

Statement, Statement-R, Executive, Envelope, Freesize (3-7/8" x 5-7/8

to 11-3/4" x 17") 17 lb. to 32 lb. Bond

Acceptable Paper Weight: Paper Capacity Per Tray

Staple Mode:

Non-collate, Collate, Group Mode: 1,000 Sheets (Letter, Statement-R,

500 Sheets (11" x 17", Legal,

Letter-R) 1,000 Sheets/30 Sets (Letter,

Executive)

500 Sheets/30 Sets (11" x 17",

Legal, Letter-R)

Corner Staple, Double-Staple

50 Sheets (Letter, Executive) Max. Stapling Capacity: 30 Sheets (11" x 17", Legal,

Letter-R)

Saddle-Stitching\*

Folding:

Staple Positions:

Acceptable Paper Sizes: 11" x 17", Legal, Letter-R Saddle-Stitch Capacity: 15 Sheets (60 Page Booklets) Tray Capacity: 25 Sets (1 to 5 Sheets)

15 Sets (6 to 10 Sheets) 10 Sets (11 to 15 Sheets) V-Folding

Dimensions (H x W x D)

Finisher-AE1: 40-7/8" x 25-3/8" x 25-7/8" (1037mm x 643mm x 657mm) Saddle Finisher-AE2: 40-7/8" x 29-3/8" x 25-7/8" (1037mm x 747mm x 657mm)

Additional Finisher

Installation Space (W x D):

Finisher-AE1:

59-3/8" x 27-5/8"

(1058mm x 700mm) (When Stack Bypass and Auxiliary Tray are

Extended)

Saddle Finisher-AE2: 63-1/4" x 27-5/8" (1607mm x 700mm) (When Stack Bypass and

Auxiliary Tray are Extended)

Weight:

Finisher-AE1: Approx. 95.2 lb. (43.2kg) Saddle Finisher-AE2: Approx. 161 lb. (73.2kg) Puncher Unit-M1 Attachable Accessories:

Puncher Unit-M1 (Option for Finisher-AE1/Saddle Finisher-AE2)

11" x 17", Legal, Letter, Letter-R Acceptable Paper Sizes: Acceptable Paper Weight: 17 lb. to 32 lb. Bond

Punch Type

Two Holes: Legal, Letter-R Three Holes: 11" x 17", Letter Punch Waste Capacity: Approx. 3,000 Sheets 37-1/8" x 4-1/4" x 24-1/4" Dimensions (H x W x D): (941mm x 107mm x 615mm)

Weight: Approx. 15.9 lb. (7.2kg)

UFR II/PCL Printer Kit-S1

CPU: Canon Custom Processor 512MB (Standard) Memory: 768MB (Maximum) (Shared)

Hard Disk Drive: 20GB (Shared)

10/100Base-TX (RJ-45), USB 2.0 Interface Connections: High Speed

Supported PDL: UFR II, PCL 5e, PCL 6

Maximum Print Resolution: 2,400 x 600 dpi (Interpolated)

**Printer Drivers** 

UFR II: Windows® 2000/XP; Windows

Server 2000, Citrix MetaFrame, Macintosh® OS X (OS 10.1.5

PCL 5e/6: Windows 98/Me/2000/XP

Windows NT 4.0/Server 2003 Citrix MetaFrame

80 Scalable Fonts, 30 Barcode, Internal Fonts: 10 Bitmap, 2 OCR Fonts

10/100 Base-TX (RJ-45), USB 2.0 Interface Connections:

High Speed

Novell® NetWare® v.3.2, 4.1, 4.11, **Network Operating Systems:** 

4.2, 5, 5.1, 6.5 (IPX/SPX) Windows 98, Me, 2000, XP, Server 2003 (TCP/IP) Apple® Macintosh OS 8.0 or

Higher (DDP) Solaris™ 1.5x, 2.5x, or Later (TCP/IP)

Accessory: PS Printer Kit-S1 PS Printer Kit-S1 (Option for UFR II/PCL Printer Kit-S1)

512MB (Standard) Memory:

768MB (Maximum) (Shared)

Hard Disk Drive: 20GB (Standard) (Shared)

Interface Connections: 10/100Base-TX (RJ-45), USB 2.0

High Speed

Supported PDL: PostScript 3 Emulation

Maximum Print Resolution: 2400 x 600 dpi (Interpolated)

Printer Drivers Windows 98/Me/2000/XP

Windows NT 4.0/Server 2003 Citrix MetaFrame Macintosh OS X (OS 10.2

or Later)

Internal Fonts: 136 Scalable Fonts

Network Operating Systems: Windows 98, Me, 2000,

XP, Server 2003 Apple Macintosh OS X (10.2.8 or Later)

**Universal Send Kit-G1** 

Address Book Capacity: Max. 1,800 Destinations Max. 5 LDAP Servers

E-mail, I-Fax, File Server (FTP, Sending Methods: SMB, IPX, WebDAV), User Inbox,

Super G3 (Optional)

Communication Protocol File: FTP (TCP/IP), SMB (TCP/IP), NCP

(IPX), WebDAV

E-Mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

Data Format

I-Fax:

File/E-Mail: TIFF, PDF, PDF (OCR),\*\* Encrypted

PDF,\*\*\* Digital Device Signature PDF,\*\*\* Digital User Signature PDF

TIFF (MH, MR, MMR)

Super G3 Fax Board-Q1/Super G3 Multi-Line Fax Board-D1

Applicable Line: Public Switched Telephone Network (PSTN)

Connection Lines: One-Line (Super G3 Fax Board-Q1)

Two-Lines (Super G3 Multi-Line

Fax Board-D1)

Sending/Original Size: Statement to 11" x 17" Receiving/Printing Size: Statement to 11" x 17"

Transmission Times

ECM-MMR: Approx. 3.2 Seconds/Page G3MR/G3MH: Approx. 13 Seconds/Page IBIG: Approx. 2.6 Seconds/Page Auto Dial Function: Address Book 1,800 Destinations

(Including Destinations Stored in

One-Touch Buttons)



## **OTHER OPTIONAL ACCESSORIES**

• imageRUNNER 256MB

Expansion RAM-B1

Secure Watermark-A1

HDD Data Erase Kit-A1

· Expansion Bus-B1

Board-G1

· eCopy Suite

Kit-A2

• HDD Data Encryption Kit-B4

USB Application Interface

Voice Operation Kit-A1<sup>††</sup>

imageWARE™ Suite

· Remote Operator's Software

- Cabinet-P1
- FL Cassette-Y1 (Replacement)
- FL Cassette-Z1 (Replacement)
- · Envelope Feeder Attachment-C2
- Copy Tray-J1
- Document Tray-J1
- Card Reader-C1
- Card Reader Kit-B1
- Braille Label Kit-A1
- ADF Access Handle-A1
- Workflow Composer-A1
- Encrypted Secure Print Software-C1
- Barcode Printing Kit-A1<sup>▲▲</sup>
- Web Access Software-F1<sup>†</sup>
- Digital User Signature PDF Kit-A1
- Universal Send PDF Security Feature Set-A1\*\*
- Universal Send Searchable PDF Kit-A1<sup>†††</sup>

- \* Available with Saddle Finisher-AE2 only.
- \*\* Requires Universal Send Searchable PDF Kit-A1.
- \*\*\* Requires Universal Send PDF Security Feature Set-A1.
- ▲ Requires Digital User Signature PDF Kit-A1.
- \*\* Requires the UFR II/PCL Printer Kit-S1.
- † Requires the imageRUNNER 256MB Expansion RAM to display Web Flash content. Requires the UFR II/PCL Printer Kit-S1 for printing functions. Add the PS Printer Kit-S1 if printing PDF files.
- <sup>††</sup> Requires imageRUNNER 256MB Expansion RAM-B1.
- \*\*\* Requires Universal Send Kit-G1



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries. PostScript is a registered trademark or trademark of Adobe Systems Incorporated in the United States and/or other countries. Apple and Macintosh are trademarks of Apple Computer, Inc. Novell and Netware are registered trademarks of Novell, Inc. in the United States and other countries. Solaris is a trademark or registered trademark of Sun Microsystems, Inc. in the United States and other countries. CANON and IMAGERUNNER are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other coun-

istered trademark or trademark in other countries. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All referenced product names and other marks are trademarks of their respective owners.

Specifications and availability are subject to change without notice.

Some products shown with optional accessories and equipment. Actual product configurations may differ. ©2007 Canon U.S.A., Inc. All rights reserved.

tries. RAPID FUSING SYSTEM is a trademark of Canon Inc. in the United States and may also be a reg-

0707R-3045-PDF-NW







1-800-OK-CANON www.usa.canon.com

Canon U.S.A., Inc. One Canon Plaza Lake Success, NY 11042